

FOU-NR120-5G



FOU-NR120-5G is a wireless communication router for the Internet of Things, which uses public 3G/4G/5G networks to provide users with wireless long-distance big data transmission functions.

The product uses high-performance industrial-grade 32-bit communication processors and industrial-grade wireless modules, with embedded real-time operating system as the software support platform, and provides 1 RS232 (or RS485), 1 Ethernet LAN, and 1 Ethernet WAN (or LAN), can connect serial port, CAN port device, Ethernet device and WIFI device at the same time, realize data transparent transmission and routing function.

The product has been widely used in the M2M industry in the IoT industry chain, such as smart grid, smart transportation, smart home, supply chain automation, industrial automation and other fields.

Topology



Features

Industrial Design

- ◆ High-performance industrial-grade cellular module
- ◆ High-performance industrial-grade 32-bit communication processor
- ◆ Using metal shell, protection grade IP30
- ◆ Wide power input range (DC 9~36V)

Reliable

- ◆ WDT Watchdog design
- ◆ Complete anti-dropping mechanism to ensure that the data terminal is always online
- ◆ Built-in 1.5KV electromagnetic isolation protection for Ethernet interface
- ◆ RS232/RS485 interface: Power and data isolation, in line with CSA, UL and IEC standards
- ◆ SIM/UIM card interface built-in 15KV ESD protection
- ◆ Built-in reverse phase protection and over voltage protection for the power interface

Standard

- ◆ Standard RS232/RS485, CAN port Ethernet and WIFI
- ◆ Provide standard wired WAN port (support standard PPPOE protocol)
- ◆ Plug and Play
- ◆ Multiple working mode options
- ◆ Configuration and maintenance interface (including local and remote WEB mode or CLI mode)
- ◆ Support DIN rail, wall-mounted installation

Functions

- ◆ Multiple WAN connection methods, Including static IP,DHCP,PPPOE,3G/UMTS/4G/LTE,DHCP-4G/5G
- ◆ Support 3G/4G/5G and wired WAN dual link backup function (optional)
- ◆ Support VPN (PPTP,L2TP,IPSEC,OPENVPN,GRE)
- ◆ Support remote management,SYSLOG、SNMP、TELNET、SSH、HTTPS
- ◆ Support local and remote online upgrade
- ◆ Support import and export configuration files
- ◆ Support NTP,Built-in RTC
- ◆ Support DDNS
- ◆ Support VLAN, MAC address clone
- ◆ WIFI Support 802.11b/g/n/ac,Support AP/AP Client/Bridge mode
- ◆ WIFI Support WEP, WPA, WPA2 and other encryption methods,
- ◆ Support Private APN sim card
- ◆ Support DHCP server and DHCP client,NAT,DMZ,QOS,Traffic statistics, real-time display of data transmission rate
- ◆ Support TCP/IP、UDP、FTP (optional)、HTTP and other network protocols
- ◆ Support SPI firewall, VPN pass through,ACL,URL filter
- ◆ Support hardware encryption (optional)

Cellular

Project	Content
Wireless	Industrial wireless module
Frequency	5G NR: n1/n2/n3/n5/n7/n8/n20/n28/n41/n66/n71/n77/n78/n79 LTE:B1/B2/B3/B4(66)/B5(18/19/26)/B7/B8/B12(17)/B13/B14/B20/B25/B26/B28/B29/B30/ B38/B39/B40/B41/B42/B43/ B46/ B48/B71 Remarks: Different modules support different network standards
Bandwidth	5G NR: DL 3.4Gbps,UL 350Mbps LTE Cat20: DL 2.0Gbps,UL 150Mbps HSPA+: DL 42Mbps,UL5.76Mbps
Power	<23dBm
Sensitive	<-97dBm

WIFI

Project	Content
Frequency	IEEE802.11b/g/n,2.4G,AP mode,Station mode (option) IEEE802.11ac,5.8G,AP mode,Station mode (option)
Bandwidth	IEEE802.11b/g: 54Mbps IEEE802.11n: 300Mbps IEEE802.11ac: 866Mbps
Encryption	WEP、WPA、WPA2
Power	26dBm (11b) ,21dBm (11ac/MCS7/HT40) ,20dBm (11ac/MCS9/HT80)
Sensitive	<-72dBm@54Mbps

Hardware

Project	Content
CPU	Industrial 32 bit processor
FLASH	Nor flash 16MB,nand flash 128MB
DDR3	512MB

Interface

Project	Content
WAN	1*10/100/1000M Ethernet (RJ45) , Auto MDI/MDIX,Built-in 1.5KV electromagnetic isolation protection Remarks: Can be used as LAN port
LAN	1*10/100/1000M Ethernet (RJ45) , Auto MDI/MDIX,Built-in 1.5KV electromagnetic isolation protection
Serial	1*RS232/RS485,Built-in 1.5KV electromagnetic isolation protection Data bit: 5、6、7、8 Stop bit: 1、1.5(option)、2 Check: NONE、EVEN、ODD、SPACE(option)

	Baud rate: 2400~115200bits/s
CAN	1*CAN2.0
Indicators	"WIFI", "Online", "PWR", "SYS"
Antenna	Cellular: 4 standard SMA female antenna interfaces, characteristic impedance 50 ohms WIFI: 2 standard SMA male antenna interfaces, characteristic impedance 50 ohms GPS: 1 calibrated SMA female antenna interface, characteristic impedance 50 ohms (optional)
SIM/UIM	Standard drawer type user card interface, support 1.8V/3V SIM/UIM card, built-in 15KV ESD protection, support dual SIM card
Power	Terminal power socket
Reset button	Through this button, the parameter configuration can be restored to the factory value

Power supply

Project	Content
Standard	DC 12V/1.5A
Range	DC 9~36V
Consumption	<1.2A (12V)

Physical

Project	Content
Shell	Metal shell, protection grade IP30
Size	135*110*43mm (Does not include antenna and mounting parts)
Weight	500g

Others

Project	Content
Operating	-35~+75°C (-31~+167°F)
Storage	-40~+85°C (-40~+185°F)
humidity	95%(No condensation)

GPS (option)

Project	Content
GPS module	Industrial GPS module
Receiver type	50 channels, GPS L1 (1575.42MHz) C/A code Support WAAS, EGNOS, MSAS, GAGAN, compatible with GALILEO
Maximum update rate	4Hz
Accuracy	Locate: 2.5mCPE SBAS: 2.0mCPE
Capture	Cold start: 29S Warm start: 29S Auxiliary start: <1S Hot start: <1S

Sensitive	Tracking: -160dBm Recapture: -160dBm Cold start: -144dBm
Timing accuracy	RMS: 30ns 99%: <60ns Graininess: 21ns
Time pulse	0.25~1000Hz
PPS	Support, the rising edge of the pulse is aligned with UTC time

Order info

Model	Content
FOU-NR120-5G	Cellular (5G NR), 2.4G/5G WIFI, SIM*2 , GPS(option)