



Features:

- 15.0" TFT LCD, LED Backlit, XGA 1024*768;
- Aluminum-magnesium alloy, Anodized treatment, modular designed;
- High temp. 5-wires precision resistive touchscreen, EETI controller;
- Default USB touch interface, optional with RS232 touch interface;
- DC 12V power input, optional with wide voltage DC 9~36V;
- Multiple DVI + VGA signal input, support synchronous and asynchronous display;
- Panel mount, support VESA 75/100 mount, Front surface IP65 rate protection.


Specification

Basic	Front panel	Magnesium-Aluminum alloy, anodized treatment
	Real panel	SGCC plate sheet, sand-blasting
	Control button	OSD button on rear panel
	Signal input	1* VGA, 1* DVI
	Mount method	Panel mount, support VESA 75/100 mount
	Overall dimension	352.2 * 279.3 * 51 (mm)
	Cut-out dimension	341 * 268 (mm)
	Net weight	3.0KG
	IP rate	Front surface IP65
LCD Display	Size/Type	15.0" TFT LCD Display
	Resolution	1024 * 768 (XGA)
	Brightness	350 nits
	Contrast ratio	900:1
	Backlit & MTBF	LED backlit & 50 000 hours
	Display area	304.128 * 228.096
	View angle	80/80/80/80
Touchscreen	Type	High temp. 5-wires precision resistive touchscreen
	Touch interface	USB (Optional RS232)
	Click life	250g/ 35 million times
	Draw life	250g/ 5 million times
	Special treatment	PET film laminated, flat design
	Touch controller	EETI
Power & Environmental	Operating temp.	-20 ~ + 70 (°C)
	Storage temp.	-30 ~ + 80 (°C)
	Relative Humidity	10 ~ 95% @ 10C (No condensation)
	Vibration	50 ~ 500 Hz, 1.5G, 0.15mm peak to peak
	Shock	10G/Peak (11 ms)
	Power input	DC 12V (Optional wide voltage DC 9~36V)
	Power consumption	About 20W
	EMC	CE/FCC Class A

EAGLE-TA-M-PR150W

Panel mount Industrial Monitor

Dimension Unit:mm



DIMENSIONS IN MILLIMETERS

EAGLE-TA-M-PR150W

Ordering info.

Part no.	Description
EAGLE-TA-M-PR150W	15.0" LCD, 1024*768, Resistive touch, USB interface, 1*VGA, 1*DVI , DC 9~36v (default no PSU)
	HDMI to DVI convert cable, 1.8m length
	DVI cable, 1.8m length
	COM cable, around 1.8m length (For TM-PR150S)
	40W power supply (For EAGLE-TA-M-PR150W)

Packing List

1x Standard Product
1x USB cable (For touch), 1.8m length
1x VGA cable, 1.8m length
1x Power cable & Plug
8x Panel mount metal clips



ErreUno S.r.l.

Via Novella ,13
43058 Sorbolo (PR) Italy
Tel : +39 / 0521 694164
Fax: +39 0521-1851863
email: info@erre1.it
P.I / CF : 02379290345