

6 views



Specifiche tecniche

Product Form	10.1-inch Vehicle PC
Material	PC+TPU
Dimensions	274.9*188.7*22.2mm
Weight	1140g
Product Color	Black
CPU	Intel Alder LAKE N100
GPU	Intel® UHD Graphics
Memory	RAM 8GB LPDDR5 Optional: 16G ROM 128GB EMMC
Operating System	Windows 11 Home
Display	Type: IPS Size: 10.1 inch 16:10 Resolution: 1200*1920 Brightness: 1000cd/m ²
Touch Panel	10-Point Capacitive Screen, G+G, Panda Glass, Hardness Above 7H, Scratch-Resistant, COF, Supports Glove Touch
Camera	Front 5.0MP Rear 8.0MP
Buttons	Power *1 Volume + Key *1 Volume - Key *1 P1 Key *1 (HOME Key) F Key *1 (Barcode Scanning, Connected to GPIO)
Speaker	Built in 8Ω/1W Waterproof Speaker *2
Microphone	Sensitivity: -42dB, Output Impedance: 2.2kΩ

Battery	Removable Polymer Lithium-ion Battery 7.6V/5000mAh 6.5hrs (Tablet product testing conditions: screen brightness of 30%, 300nit, volume of 22%, 30cm70db volume, screen long on, playing 1080P video)
RTC	3V 1mAh Rechargeable Surface-Mount
G-Sensor	G-Sensor
WIFI	WIFI6 802.11(a/b/g/n/acR2/ax 1x1) Frequency: 2.4G+5.8G Dual-band WIFI intel AX101
蓝牙	BT5.2 (BLE)
2G	NA
3G	WCDMA: B1/5/8
4G	EURO: LTE FDD: B1/B3/B5/B7/B8/B20/B28 LTE-TDD B38/B40/B41
GPS	Supports GPS, Glonass; Capture Sensitivity: -140 dBm; Cold Start Time: <50 seconds, Hot Sstart Time: <5 seconds; GPS Frequency: 1575.42MHz Optional: GPS + BeiDou
Fingerprint	Standard
2D	Optional:Hardware Decoding Optical Resolution: 5mil Scanning Speed: 50 scans/s Supported Barcode Types: PDF417, MicroPDF417, Data Matrix, Data Matrix Inverse Maxicode, QR Code, MicroQR, QR Inverse, Aztec, Aztec Inverses, Han Xin, Han Xin Inverse
NFC	Optional: NXP300/NFC 13.56MHz Supports 14443A/14443B/15693/18092/mifare protocols of ISO/IEC
I/O Interfaces	USB 3.0 *1 (Type A) Type C *1 (Data & Charing) φ 3.5mm Standard Earphone Jack *1 TF *1 SIM Card *1 DC 12V 4A Power Port x1 (Male Plug outer diameter 5.5mm) HDMI 2.0 mini *1 12PIN Pogo Pin *1
Choose 1 from 3	USB 2.0 *1 (4pin) RJ45 Adaptive, Recognizes 1000M Network Card (Standard) RS232 Serial Port
Adapter	AC100V to 240V, 50Hz/60Hz output DC 12V/4A wall plug European Standard, with CE Certification Optional: US Standard, Chinese Standard, UK Standard
Rugged Features	MIL-STD-810H: 1.22m drop resistance Working temperature: -20 °C to 60 °C Storage temperature: -30 °C to 70 °C Humidity: 95% Non-Condensing

Certifications	IP65
	CE NB
	FCC (know the real situation)
	RoHS
	CCC (know the real situation)
	MIL-STD-810H
	Battery: UN38.3, MSDS, Air and Maritime Reports, IEC62133
Accessories	DC 12V 4A Adapter x1 (Male Plug Outer Diameter 5.5mm) (Standard)
	Hand-Strap (Standard) 
	Docking Charger DC87 (Optional) 
	Vehicle Mount VUM17J (Optional) Requires a 5.5mm to 4mm DC Adapter Cable 
	Removable 7.6V 5000mAh Battery (Optional) 
	19V/3A Car Charger, Cigarette Lighter Adapter, Male Plug Outer Diameter 5.5mm (Optional) 
 www.erre1.it info@erre1.it 	